WOLSELEY

SPRING2018

PUMPS AND WATER TREATMENT

PROFLO

3 YEAR WARRANTY

1/3 HP SUBMERSIBLE THERMOPLASTIC SUMP PUMP WITH BASE

PF92330PB

- For typical residential and commercial applications
- Maximum head of 25'
- 1/3 HP permanent split capacitor motor
- Tethered float switch
- Thermoplastic impeller

PROFLO

3 YEAR WARRANTY

1/2 HP CAST IRON SEWAGE PUMP WITH FLOAT SWITCH

PF93501

- For typical residential and commercial applications where materials must be moved upward from a basin to sewer or septic lines or to drainage fields
- 7.6 amps, 912 watts
- Maximum flow rate of 80 gpm
- 2" Solids handling ability
- Discharge size 2" FNPT
- Cast aluminum vortex impeller

PROFLO

3 YEAR WARRANTY

1/3 HP THERMOPLASTIC SUBMERSIBLE SUMP PUMP WITH FLOAT SWITCH

PF92370

- For typical residential and commercial applications
- Wide Angle Mechanical Float Switch, Pump Mounted
- 4.1 amps, 492 watts.
- Discharge size 1-1/2" FNPT

PROFLO

5 YEAR WARRANTY

0.3 HP SUBMERSIBLE CAST IRON SUMP PUMP

PF92341

- For typical residential and commercial applications
- Contains side discharge 1-1/2" FNPT
- 4.1 amps, 492 watts
- Permanent split capacitor motor
- SJE Rhombus vertical float switch
- Stainless steel impeller

PROFLO

3 YEAR WARRANTY

0.3 HP SUBMERSIBLE CAST IRON SUMP PUMP WITH FLOAT SWITCH

PF92331

- For typical residential and commercial applications
- Maximum head of 25'
- Permanent split capacitor motor
- 4.1 amps, 492 watts
- Discharge size 1-1/2 FNPT, Tethered float switch
- General water transfer, fountains and ponds, farm use and basement drainage

PROFLO

3 YEAR WARRANTY

SIMPLEX SEW PUMP KIT WITH PF93501 PUMP

PF93015

- For typical residential and commercial applications
- Simplex pre-assembled system includes: Cast iron sewage pump, 18" x 30" structural foam basin with cover and 2" x 30" PVC pipe
- Handles 2" solids
- Maximum head of 25'
- 1/2 HP permanent split capacitor motor
- Cast aluminum vortex impeller
- For movement from a basin to sewer or septic lines or to drainage fields

WOLSELEY
The best local distributor

ABOUT US
wolseleyinc.ca

SHOP ONLINE
wolseleyexpress.com

3 YEAR WARRANTY

SEWAGE PUMP KITS

PF93024 - PF93026

Pre-assembled kit is ready for installation

Pump Features

- Kit PF93024 includes pump PF93501 pump
- Kit PF93026 includes pump PF93511 pump
- 1/2 HP continuous duty, thermally protected split capacitor motor
- Tethered or vertical float switch
- Rugged cast iron construction
- Stainless steel, non-clogging vortex impeller
- Will easily handle 2” solids
- Pumps will lift water up to 25’ of vertical height
- 2” discharge for high capacity pumping
- 80 gallons per minute / 4800 gallons per hour

Basin Features

- Tough polyethylene construction
- Corrosion resistant
- 24” x 24” - 45 gallon capacity
- Gasket sealed liquid and airtight cover with 8 bolts
- Built-in anti float collar prevents basin from floating
- Pre-plumbed with 2” PVC
- 2” NPT discharge and vent
- Integrated 360° lifting handle
- Molded torque stops prevent pump from turning

PF93024

PF93026

3 YEAR WARRANTY

SEWAGE PUMP KITS

PF93082 - PF93084

Pre-assembled kit is ready for installation

Pump Features

- Kit PF93082 includes PF93782 pump
- Kit PF93084 includes PF93781 pump
- 1/2 HP continuous duty, thermally protected split capacitor motor
- Tethered or vertical float switch
- Stainless steel and cast iron construction
- Stainless steel, non-clogging vortex impeller
- Will easily handle 2” solids
- Pumps will lift water up to 30’ of vertical height
- 2” discharge for high capacity pumping
- 140 gallons per minute / 8400 gallons per hour

Basin Features

- Tough polyethylene construction
- Corrosion resistant
- 24” x 24” - 45 gallon capacity
- Gasket sealed liquid and airtight cover with 8 bolts
- Built-in anti float collar prevents basin from floating
- Pre-plumbed with 2” PVC
- 2” NPT discharge and vent
- Integrated 360° lifting handle
- Molded torque stops prevent pump from turning

PF93082

PF93084

3 YEAR WARRANTY

JET PUMPS

- Cast iron pump body for durability
- Pre-mounted, fully adjustable pressure switch
- Built-in thermal overload protection for safety
- Glass filled thermoplastic impeller and diffuser
- Dual voltage 115/230 volts

PF94505	1/2 HP Shallow Well Jet Pump
PF94515	1/2 HP Convertible Jet Pump
PF94705	3/4 HP Shallow Well Jet Pump
PF94715	3/4 HP Convertible Jet Pump

PF94505 / PF94705

PF94515 / PF94715

1 YEAR WARRANTY

CHECK VALVES - PVC

MODEL	DESCRIPTION	INLET	OUTLET
PFPCVC300J	1-1/2” compression check valve	1-1/2” compression	1-1/2” compression
PFPCVC300K	2” compression check valve	2” compression	2” compression
PFPCVC500HJ	1-1/2” or 1-1/4” sump pump check valve	1-1/4” or 1-1/2” compression	1-1/4” or 1-1/2” compression
PFPCVS400K	2” check/ball valve combination	2” socket (Union)	2” socket (Union)

PFPCVC300J PFPCVC300K PFPCVC500HJ PFPCVS400K