



The HH Series

Horizontal Slab Coil

Coil Model 13 SEER	Nominal Tonnage	Overall		Plenum		Weight (lbs)	Skid QTY
		Width	Height	Width	Height		
HH57118A185A2102AP	1.5	23"	22 ³ / ₄ "	18 ⁵ / ₈ "	21 ¹ / ₄ "	36	6
HH58124A225A2102AP	2	27"	22 ³ / ₄ "	22 ⁵ / ₈ "	21 ¹ / ₄ "	41	4
HH59130A265A2102AP	2.5	31"	22 ³ / ₄ "	26 ⁵ / ₈ "	21 ¹ / ₄ "	44	4
HH59136A265A2102AP	3	31"	22 ³ / ₄ "	26 ⁵ / ₈ "	21 ¹ / ₄ "	44	4
HH61148A365A2102AP	4	41"	22 ³ / ₄ "	36 ⁵ / ₈ "	21 ¹ / ₄ "	57	3
HH66160A425A2102AP	5	47"	22 ³ / ₄ "	42 ⁵ / ₈ "	21 ¹ / ₄ "	75	3

TX Valves	
65616201	R22 Non-bleed AC/HP 1-3 Ton
65616202	R22 Non-bleed AC/HP 3½-5 Ton
65616601	R-410A Non-bleed AC/HP 1-3 Ton
65616602	R-410A Non-bleed AC/HP 3½-5 Ton

NOTES:

- Bi-directional airflow
- Refrigeration connections are 3/8" liquid and 7/8" suction
- These specifications are for sweat connection "Horizontal" coils
- Depth on all coils is 10"
- TX Valve may be required on 13 SEER coil applications**



Additional Benefits

- High efficiency lanced fin design
- "No-hassle" 5 year warranty
- R-410A, R-22, A/C & heat pump compatible
- All coils have durable packaging with bar coded labels on the box
- Threaded expansion valves available factory installed or as a field installed kit
- Coils are air pressure tested at 500 PSI, leak tested with Helium, sealed with rubber plugs, then charged with dry air
- Piston options include externally accessible body for easy piston change out and/or TXV installation
- Liquid line refrigerant connections are 3/8" ODF
- Suction line refrigerant connections are 7/8" ODF

